

PSW-A224

24 Port PoE Switch



Key Features

- 24-Port 10/100Mbps + 2 gigabit Copper/SFP Combo uplink Port unmanaged POE Switch
- 24 -Port supply power to POE Powered Device
- Complies with the IEEE 802.3af/at standard
- Each switch port support auto-negotiation-10/20, 100/200Mbps (Fast Ethernet), 1000/2000Mbps (Gigabit Ethernet).
- Support MAC address auto-learning and auto-aging
- Prevents packet loss with back pressure (Half-duplex) and IEEE 802.3x PAUSE frame flow control (Full-duplex)
- High performance Store and Forward architecture, broadcast storm control, runt / CRC filtering eliminates erroneous packets to optimize the network bandwidth
- Non-blocking switching architecture that forwards and filters packets at full wire-speed for maximum throughput
- 8.8 GBPS Switching Capacity
- On/Off power switch

Specification

Product name	24-ports unmanaged POE switch
Order No.	PSW-A224
Network protocols and standards	<ul style="list-style-type: none">- IEEE 802.3 10BASE-T- IEEE 802.3u 100BASE-TX- IEEE 802.3ab 1000BASE-T- IEEE 802.3z 1000BASE-X- IEEE 802.3x Flow Control- IEEE 802.3af/at Power over Ethernet
Power Specifications	<ul style="list-style-type: none">- Power consumption: maximum 440W- Voltage: 100 - 240 VAC, 50 -60 Hz
Network interface	<ul style="list-style-type: none">-24 10/100M ports (MDI / MDIX adaptive); ports with PoE features (24)-2 10/100/1000Mbps Gigabit copper RJ45 ports (MDI / MDIX adaptive)- 2 10/100/1000Mbps SFP GBIC fiber module slots
Physical Specifications	<ul style="list-style-type: none">- Weight: 5kg
Electromagnetic radiation	<ul style="list-style-type: none">- CE mark, commercial- FCC Part 15 Class A- VCCI Class A- C-Tick